

COUNTY CHAVES FIELD Calc

STATE NM MAP

OPR PAN AMERICAN PETROLEUM CORP.

6 Wasley

Sec. 14, T-8-S, R-30-E

1980' FML, 1980' FWL of Sec.

Spd 7-24-67

Cmp 8-2-67

CSG & SX - TUBING

FORMATION	CLASS	DATUM	FORMATION	EL	DATU
8 5/8"	254'	250			
4 1/2"	3610'	300			

LOGS EL GR RA IND HC A

IP San Andres Perfs 3444-3490' Swd & Flwd 254' EOPD. Pot.

Based on 20 hr test of 270 EO + 35 ELW thru 20/64" shk., TP

125#, CP 350#, Gravity 25.3, GOR 622.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drilg. Co.

DATE

PROP DEPTH 3600'

TYPE RT

7-24-67 F.R. 7-20-67; Opr's Elev. 3124' RS

7-31-67 PD 3600' - SA

8-7-67 Contr. - Cactus

MI Rot.

TD 3610', prep to run casing.

TD 3610', PRD 3590', COMPLETE.

Perf 3444-3490' W/2 SPF

Acid (3444-3490') 3000 gals 29% +

1500 gals treated wtr.

LOG TOPS: Yates 1630', Queen 1200',

San Andres 2670'.