

9-5-67 TD 4448', PBD 4426', TOP
Pmpd 48 BLO + 102 BW in 72 hrs.
9-11-67 TD 4448', PBD 4426', pmpg load.
9-18-67 TD 4448', PBD 4426', pmpg load.
Pmpd 3 BLO in 24 hrs (-273 BLO)
9-25-67 TD 4448', PBD 4426', pmpg load.
Pmpd 6 BLO in 24 hrs (-225 BLO)
10-2-67 TD 4448', pmpg load.
10-9-67 TD 4448', PBD 4426', pmpg load (-184 BLO)
10-16-67 TD 4448', PBD 4426', pmpg load.
10-23-67 TD 4448', PBD 4426', pmpg load. (-159 BLO)
10-30-67 TD 4448', PBD 4426', pmpg load.
11-6-67 TD 4448', PBD 4426', WO Pot.
Pmpd 12 BLW + 10 BNO in 24 hrs.

11-13-67 TD 4448', PBD 4426', COMPLETE
LOG: Rustler 1974', Yates 2362', Queen
3067', San Andres 3564', Pi Zone 4104'.

COUNTY	CHAVES	FIELD	Chaveroo	STATE	NM
OPR	SUNRAY DX OIL CO.				MAP
	5 New Mexico "X" Federal				
	Sec. 10, T-8-S, R-33-E				CO-ORD
	1980' FNL, 1980' FEL of Sec.				30-005-20110
	Spd 7-17-67		CLASS	EL [REDACTED]	
	Cmp 11-7-67		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
8 5/8"	347'	200			
4 1/2"	4447'	200			
LOGS EL GR RA IND HC A					
			TD 4448', PBD 4426'		

IP San Andres Perfs 4271-4358' Pmpd 13 BOPD + 6 BW. Pot.
Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4450' TYPE RT
DATE

F.R. 7-20-67; Opr's Elev. 4400' KB
PD 4450' - SA
7-24-67 Drlg. 2250'.
7-31-67 TD 4448', WOC.
8-7-67 TD 4448', PBD 4426', swbg.
Perf @ 4271', 4280', 4306', 4311', 4336',
4347', 4354', 4358' W/l SPI
Acid (4271-4358') 2000 gals.
Frac (4271-4358') 27,000 gals oil + 33,000#
sd.
8-14-67 TD 4448', WO Elect.
8-21-67 TD 4448', WO Elect.
8-28-67 TD 4448', SD Pump Repairs.