Form	9-331
(Mat	1963)

SHOOT OR ACIDIZE

	200.4
SUBMIT IN TRIPI	TI
(Other ligstractions)	1

SHOOTING OR ACIDIZING

r instructions aide)	re-	Budget Bureau No. 42 R1424. 5. LEASE DESIGNATION AND SERIAL NO.
		104-0177517

	UN TO STATES SUBMIT IN TRIPI TE (1963) DEPARTMENT OF THE INTERIOR verse side)	5. LEASE DESIGNATION !	r No. 42 R1424.
MOCC_	GEOLOGICAL SURVEY	100-0177517	
NMOCC BLM - S	ANTA TE use this for proposals to drill or to despin of the back to a different reservoir. ANTA TE use this for proposals to drill or to despin of the back to a different reservoir.	6. IF INDIAN, ALLO TER. 7. UNIT AGREEMENT NAM	
	WELL GAN WELL STHER Drilling	1. CAIT AUREEMENT NA	
2.	Pan American Petroleum Corporation	6. FARM OR LEASE NAME Cato "B" Federal	
3.	Box 68 - Hobbs, N.M. 88240	9. WELL NO.	
	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Cato San Andres	
6	.60' FNL & 1980' FWL Sec. 23 (Unit C, NE/4 NW/4	11. SEC., T., R., M., OR IN SURVET OR AREA 23 - 8 - 30	
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	
		Chaves	N.M.
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or O		
	NOTICE OF INTENTION TO:	ENT REPORT OF:	
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF X FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	REPAIRING W	

er)

Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.).

Chico Drilling Co. spudded 12 1/4" hole 10:00 AM 7-27-67. On 7-27-67, 8 5/8" OD 24# J-55 Casing was set @ 287' w/250 sx Incor Neat & 2% Calc. Cement Circulated. WOC 12 Hours*. Tested casing w/ 1000 psi for 30 minutes. Tested OX.

Reduced hole to 7 7/8" and resumed drilling.

ABANDON*

* Est. Vol. 450 CF Approx. Temp. of Slurry when Mixed 85° Formation Temp. 70° Est. 750 pmi est. strenght of cement @ test.

18.	I hereby certify th	at the foregoing is true and co	rrect		
;	SIGNED		TITLE _	Area Superintendent	DATE 7-28-67
	(This space for Fe	ederal or State office use)			
		APPROVAL, IF ANY:	TITLE _		DATE

O-4 USGS -Ros.

1 NSN

1 Susp 1 RRy

*See Instructions on Reverse Side

1 1967

U. S. GEOLOGICAL SURVEY ROSWELL NEW MEXICO