

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

NMOCC - ARTESIA

NMOCC - HOBBS

BLM - SANTA FE

SUMMARY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. LEASE DESIGNATION AND SERIAL NO.

NM-046153-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MILLER Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

TOM-TOM Sam And

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

34-7-31 NMPM

12. COUNTY OR PARISH

CHAVES

13. STATE

NM

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

DRILLING

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FNL x 660' FEL, Sec 34 (UNIT H, SE1/4 NE1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4343' R.D.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Cactus Drilg Co. spudded 12 1/4" hole 6:30
PM 8-16-67. On 8-17-67. 8 5/8" OD 24" J-55
casing was set @ 355' w/ 300 sy Incon
metal + 2% Cacl.* After WOC 12 hours.
Tested casing w/ 1000 psi for 30 minutes.
Test O.K.

Reduced hole to 7 7/8" @ 355' and resumed
drilling.

* EST VOL - 450 CF
APPX TEMP SLURRY, 85°
FORM. TEMP. EST. 70°
EST. STGTH CMT @ TST. 750 psi
CEMENT CIRCULATED.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE AREA SUPERINTENDENT

DATE

8-23-67

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

J. W. Sullivan* See Instructions on Reverse Side

RECEIVED

AUG 24 1967

U. S. GEOLOGICAL SURVEY
ROSWEIL, NEW MEXICO

Q 4 US 15-ROS
1- NSD
1- S/SID
1- RRY
1- UNION TEX
1- TSP