NW OIL COMS. COMMISSION

Drawer DD

NM-046153-A

Artesia, NM - 88210

5. LEASE

AUTOL VA	Philosoph			
Budget	Bureau	No.	42-R14	12

DEPARTMENT OF THE INTERIOR

UNITED STATES

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTLE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS -Do not use this form for proposals to drill or to deepon or ping back to a different reservoir. Use Form 9-331-0 for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	RECEIVED 6		
1. oil gas other Salt Water Disposal 2. NAME OF OPERAFOR Haseloff Corporation	Miller Federal 9. WELL NO. 4 10. FIELD OR WILDCAT NAM	ARTESIA, OFFI		
3. ADDRESS OF OPERATOR P. O. Box 763, Hobbs, NM 88241 4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space 17 below.) AT SURFACE: 1980' FSL & 660' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Tom Tom San Andres 11. SEC., T., R., M., OR BLK AND SURVEY OR AREA Sec. 35, T7S, R31E 12. COUNTY OR PARISH 13. STATE Chaves NM 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4338 DF			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON** (other)	(NOTE: Report results of multiple completion or zone change on Forn 9-330.)			

measured and true vertical depths for all markers and zones pertinent to this work.)*

Work began 9/11/84. Pulled tubing and packer. Found leak in $4\ 1/2"$ casing at 486'. Set retrievable bridge plug at 540' and squeezed with 175 sacks, cement circulated to surface. Drilled out cement, pulled retrievable bridge plug and tested casing with 500# for 30 minutes. Test O.K. Circulated hole clean. Ran 2 3/8" plastic coated tubing and set packer at 3181. Resumed injection 9/17/84. Well takes water on vacuum.

Subsurface Safety Valve: Manu. and Type				Set @	Ft.
18. I hereby certify that the foregoing is true a		Agent	DATE	9/19/84	
ACCEPTED FOR RECORD (THE CONDITIONS OF APPROVACNIE VANCHENIE INC.)	1				· · · · · · · · · · · · · · · · · · ·

*See Instructions on Reverse Side