N.M.O.C.D. COPY

Form Approved. Budget Bureau No. 42-R1424

STATES UNIT

Э.	LE,	LUP	
	NM	11762	
6	JE II	NDIAN ALLOTTEE OR TRIBE NAME	

DEPARTMENT OF THE INTERIOR	NM 11762		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME		
			
1. oil gas well other SWD JUL 2 6 1979	Brown A Federal 9. WELL NO.		
	2		
2. NAME OF OPERATOR Shell Oil Company	10 FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Cato (San Andres)		
P.O. Box 1509, Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
below.)	Sec. 26, T-8-S, R-30-E		
AT SURFACE: 1980' FNL and 660' FWL	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Chaves New Mexico		
	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4181' DF		
TEST WATER SHUT-OFF			
FRACTURE TREAT			
SHOOT OR ACIDIZE			
REPAIR WELL PULL OR ALTER CASING REC	change on Form 9–330.)		
MULTIPLE COMPLETE	_		
CHANGE ZONES	111 1979		
ABANDON*			
(other) U.S. GEU	LUGICAL SURVEY		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (CIARLES including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	directionally diffied, give subsurface locations and ent to this work.)*		
 Set a BP on top of perf @ 1650'. Cap B sx cmt). 			
2. Fill the hole w/salt gel mud consisting	of 10# brine w/25# of gel/bbl.		
3. Set a BP above top of salt @ 1150'. Ca	p the BP w/5 sx cmt (est 48° of		
fill for 5 sx cmt).	seeds a seed of the seed of th		
4. Cut 5½" csg from as deep as possible (±590').		
5. Spot 150 sx cmt @ stub before pulling o	incide 0.5/8" ceg		
150 sx cmt). Top of cmt must be 50' up 6. Spot cmt in 9 5/8" @surf from btm of ce	11ar down 20'		
4.00 (4.1	t 4' above GL w/"Brown A Federal		
7. Mark location w/4" OD steel pipe e leas No. 2, Sec. 26-8S-30E" welded on pipe.	2 4 above 32 w, 220wii ii		
8. Clean location.			
Subsurface Safety Valve: Manu. and Type	Set @Ft		
18. I hereby certify that the foregoing is true and correct G.W. Tull	.os		
SIGNED J. W. Tulla TITLE Senior Prod.	Eng. DATE		
(This space for Federal or State of			
APPROVED BOTIS. Sed.) ALBERT R. STALL TITACTING DISTR	ICT FINANTEEV JOE D. T. 100		
CONDITIONS OF APPROVAL, IF ANY:			