

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42 R1424.

NM000 - ARTESIA

NM000 - HOBBS

## BLM - SANTA FE SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-0177517

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CATO "A" Teekal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

CATO San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

15-8-30 NMPM

12. COUNTY OR PARISH 13. STATE  
CHAUES N.M.1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ DRUG2. NAME OF OPERATOR  
PAN AMERICAN PETROLEUM CORPORATION3. ADDRESS OF OPERATOR  
BOX 68, HOBBS, N. M. 882404. LOCATION OF WELL. (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660 FSL x 1980 FWL Sec 15, (E3-S3/4 SW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Chico Drilling Co spudded 12 1/4" hole 3:PM 9-17-67.  
At 10: PM .8 5/8" OD 24# J-55 Casing was set @ 319' w/  
250 qt. Sack + 2% CACL. Cement Circulated.  
After WOC 12 hours\* tested casing w/ 1000 psi  
for 30 minutes. Did O.K.  
Reduced hole to 7 7/8" @ 319' and resumed  
drilling.

\* EST VOL. 450 CF  
APPRX. TEMP. SURF 85°  
FORM. TEMP EST 70°  
EST STGM @ 75T 750 PSI

18. I hereby certify that the foregoing is true and correct

SIGNED

V E Staley

TITLE

AREA SUPERINTENDENT

DATE

9-18-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

014. USGS-RDS  
1-NSIO  
1-303P  
1-RRV

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

J. N. Sutherland  
District Engineer