

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

NMOC - ARTESIA

NMOC - HOBBS

BLM - SANTA FE

SECONDARY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-022636
2. NAME OF OPERATOR Shell Oil Company (Western Division)		6. IF INDIAN, ALLOTTEE OR TRIBE NAME ---
3. ADDRESS OF OPERATOR Post Office Box 1509, Midland, Texas 79701		7. UNIT AGREEMENT NAME ---
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL and 1980' FWL, Section 34, T-8-S, R-30-E, NMPM Survey, Chaves County, New Mexico		8. FARM OR LEASE NAME Hodges Federal "B"
14. PERMIT NO. --		9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4179' DF		10. FIELD AND POOL, OR WILDCAT Cato (San Andres)
		11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Section 34, T-8-S, R-30-E, NMPM Survey
		12. COUNTY OR PARISH Chaves
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Casing and Cement Test	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 2:00 PM, CDT, 9-28-67.
Cemented 14 joints (447') 8 5/8", 24#, J-55, ST&C casing at 460' with 300 sacks Class "C" cement + 2% CaCl₂.
Cement circulated. Plug down at 11:10 PM, CDT, 9-28-67.
After WOC 14 hours, tested casing to 1000 PSI for 30 minutes, no pressure drop.

Option 2:

- 354
- 300 sacks Class "C" + 2% CaCl₂.
- 60° F
- 62° F
- 600
- 14 hours

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNATURE

SIGNED BY D. L. LILLY D.L. Lilly

TITLE Division Mechanical Engineer DATE October 6, 1967

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

ACCEPTED FOR RECORD

J. N. Sutherland
Engineer

*See Instructions on Reverse Side

RECEIVED

U. S. GEOLOGICAL SURVEY
BOSTON, MASSACHUSETTS

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.