

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K2018	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator UNION TEXAS PETROLEUM CORPORATION		8. Farm or Lease Name New Mexico
3. Address of Operator 1300 WILCO BLDG., MIDLAND, TEXAS 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>8</u> RANGE <u>31</u> N.M.P.M.		10. Field and Pool, or Wildcat Tom-Tom (San Andres)
15. Elevation. (Show whether DF, RT, GR, etc.) 4328 D.F.		12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Perforations 3881'-3890', 3932'-3948', 3956'-3972', 3948'-3992', 4008'-4022'

1 - Spotted 191' cement plug (20 sx.) from 4035'-3844'

2 - McCullough ran free point; found csg. free @ 2900', Cut csg. off @2900'

3 - Pulled & laid down 93 jts. of 4½" csg.

4 - Spotted 100' cement plug (25 sx.) from 2950'-2850'

5 - Spotted 100' cement plug (25 sx.) in 7 7/8" hole from 1600'-1500' (top of salt 1550')

6 - Spotted 100' cement plug (40 sx.) from 550'-450'

7 - Spotted 10' cement plug (5 sx.) in 8 5/8" csg. top of surface

8 - Welded steel plate and installed dry hole marker.

9 - Plug and abandoned 12-19-69

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.L. Hammond TITLE Well Tester DATE 12-23-69
APPROVED BY John W. Runyan TITLE Geologist DATE Aug 22 1970
CONDITIONS OF APPROVAL, IF ANY: