

UNITED STATES

SUBMIT IN TRIPLICATE
(Other instructions: reverse side)Form approved.
District Engineer No. 42-R1424.DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDAY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FIRM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

14. PERMIT NO.

15. ELEVATIONS (Show whether BP, RT, CR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged back from Baugh to San Andres and attempted completion as follows:

1. Casing pulled 1 1/2" casing from 7143'.

2. Special plug: 100' 8200-3900' (perfs 8236-8284), 100' 7100-7053
7000-6952 4 1/2" casing @ 7148'; 100' 6555-6665; 100' 5700-5800;
100' 4600-5030' (9 5/8" casing 4500')

3. Set 2 1/2" @ 4225'.

San Andres zone - Perforated intervals 4100-64 @ 205PPF. Acidized w/ 6000 gal 15%. Evaluated same. Last 10 hours. Swab 0.2 x 0.13W. Set 1 1/2" @ 3700'. Unable to acidize perfs. Left 5' cement on top of GP. Perfs 3570-39 @ 205PPF. Acidized w/ 3000 gal 20%. Last 9 hours. Swab 1.248W. Return of oil on 10W.

Set casing & 5 1/2" perfs 3570-39 @ 125W. Drilled out to 3730'.

Perf. 3570-39 @ 205PPF. Acidized w/ 6000 gal 20%. In last 6 hours, swab 5.5W x 0.30.

All possible PAI zones evaluated - DRY HOLE.

Propose to plug as follows: (Per TELECON. Sims to Sutherland, 2-27-68)
Spot 30' plug across perfs 3570-39. 100' plug in foot of 9 5/8" casing (set top 2900')
100' across 4 1/2" @ 1352'; 100' across 1 1/2" @ 450'. 100' plug @ surface
and drill PAI area. Make final cleanup + restore ground to surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 1 1968

J. W. SUTHERLAND
DISTRICT ENGINEER

*See instructions on Reverse Side

RECEIVED
MAR 1 1968U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

OVL-0543-Ros.

1-1150

1-0052

1-229