

HMSO - ARTSIA

HMSO - ARTSIA

BLM - SANTA FE

☐ DEPARTMENT OF THE INTERIOR
☒ GEOLOGICAL SURVEY

SUNDARY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-025519

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

INCOMPLETE DRUG WELL

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

660' FSL - 660' FWL Sec. 13 (UNIT M, SW 1/4 SW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4137' R. D. B

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

WHITE Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

13-9-30 NMPM

12. COUNTY OR PARISH

CHAUVES

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Completion Attempts ☒
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged back from TD 10920 to 9908'. as follows: Spot 40Sx.
10,750-10650'; 40Sx: 10,150, 10,050'; 4 1/2" 9.5-11.6# J55 + N-80
Casing set @ 10,010' w/1500 R4 seal w/6% BTD in 1st 2500 ft. (TCMT 7153)
WOC and tested casing w/2500 psi for 30 min. Test OK. Drilled
out to 9908' and perforated. 9745-48, 9768-71 w/25PF. Acid w/
250 gal 7 1/2% MCA x 1000 gal 3% HF acid. Last 8 hours of evaluation
swab 119 BLW x Trace of Oil & Gas. Abandoned MORROW zone by
spotting a cement plug (50') from 9783'-9733' to cover perf
9745-71'. Set cast iron bridge plug @ 8400'.
Proceeding to evaluate the BOUGH zone.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE

1-25-68

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

044- USGS- Ros

1- NSW

1- SUSP

1- RRY

ACCEPTED FOR RECORD

J. W. Sutherland
District Engineer

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOSWELL, NEW MEXICO

RECEIVED

JAN 26 1968