	DEPARTME?	D STATES	C. C. COPY SUBMIT IN TRIPLIC AN Other instructions r	Form approved. Budget Bureau No. 42-R1 5. LEASE DESIGNATION AND SERIAL
		ICAL SURVEY	ION verse ander	NM 0346362 (b)
				6. IF INDIAN, ALLOTTEE OR TRIBE N.
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)				
1. OIL GAS WELL WELL	OTHEB Plug	& Abandon		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			13	8. FARM OR LEASE NAME
	nfield Company		ECEIVED	Woodman Federal
3. ADDRESS OF OPERATOR				9. WELL NO.
4. LOCATION OF WELL (R See also space 17 belo	10, Hobbs, New Ma eport location clearly and i ow.)		state requirements	2 10. FIELD AND POOL, OR WILDCAT
At surface				Cato San Andres 11. sec., T., B., M., OB BLK. AND
1980' FNL & 1980' FEL (Unit G)				SURVEY OR AREA
				00 00 000
14. PERMIT NO.	(15 ELEV.	ATIONS (Show whether DI	F RT GR etc.)	28-8S-30E 12. COUNTY OB PARISH: 13. STATE
11. IDA ALL 10.	102017		,,,,	
<u> </u>	I	4145' GR		Chaves N.M.
16. x	Check Appropriate SOTICE OF INTENTION TO:	: Box To Indicate N	Nature of Notice, Report, or	Other Data
TEST WATER SHUT-OF			WATER SHUT-OFF	ALTERING CASING
FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE C ABANDON*	UMPLAIL	FRACTUBE TREATMENT SHOOTING OR ACIDIZING	ABANDONMENT*
BEPAIR WELL	CHANGE PLA	A N 8	-	& Abandon X
(Other)	Change The		(Note: Report resu	Its of multiple completion on Well apletion Report and Log form.)
	2-3/8" tbg. Set	@ 3360'. Cia	rculated hole w/9# g	-
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C cc Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed
90 sx Cl C co Spotted 10 so Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation do and ripped in 18. I hereby certify that	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker.	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 4 ¹ " csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled
90 sx Cl C co Spotted 10 so Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	<pre>@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation</pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx Cl C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t	elled mud. Displaced 31' squeezed off. 4 ¹ " csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled
90 sx Cl C co Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 41" csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled
 90 sx Cl C co Spotted 10 sp Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	<pre>@ 3360'. Cir .ow retr. MP 4 .gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation correct </pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled FOR STATE 5/7/75 DATE 5/7/75
90 sx Cl C co Spotted 10 sx Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	@ 3360'. Cir ow retr. MP 4 gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 41" csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled
90 sx Cl C co Spotted 10 so Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED (This space for Feder APPROVED BT	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	<pre>@ 3360'. Cir .ow retr. MP 4 .gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation correct </pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled FOR STATE 5/7/75 DATE 5/7/75
90 sx Cl C co Spotted 10 so Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED (This space for Feder APPROVED BT	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	<pre>@ 3360'. Cir .ow retr. MP 4 .gel on top or H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation correct </pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 4 ¹ '' csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled FOR STATE 5/7/75 DATE 5/7/75
90 sx Cl C co Spotted 10 so Cut @ 2000' & cmt cont'g 49 8-5/8" OD csg regulation du and ripped in 18. I hereby certify that SIGNED (This space for Feder APPROVED BT	2-3/8" tbg. Set ont'g 4% gel bel x Cl C cont'g 4% & recovered. WI % gel 500'-660'. g shoe @ 290'. ry hole marker. n accordance w/B	<pre>@ 3360'. Cir .ow retr. MP 4 .gel on top or .H w/tbg OE, un Spotted 40 s POH w/tbg & s Well P&A eff BLM stipulation correct </pre>	rculated hole w/9# g 400#. Perfs 3498-35 f retr. Calculated nable to get below 6 sx C1 C cmt cont'g 4 potted 10 sk cmt plu 5/5/75. Location t ns.	elled mud. Displaced 31' squeezed off. 4 ¹ " csg free pt @ 1900' 60'. Spotted 30 sx Cl % gel 100'-300' across g @ surface. Installed o be cleaned, levelled FFC 9 % 5 0 5/7/75 DATE 5/7/75

REDENTO

(TE 25 1076

CE CONSTRUCTION COMM. 19985, R. M.