

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPLI
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

NM300 - ARIZONA



GEOLOGICAL SURVEY

NM300 - UNITED STATES SUNDRA NOTICES AND REPORTS ON WELLS

BLM - SANTA FE Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT..." for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM 0346362
2. NAME OF OPERATOR Sun Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 2792, Odessa, Texas 79760		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' from North line and 1980' from west line of Sec. 28, T8S-R30E		8. FARM OR LEASE NAME Woodman-Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4142' Gr.		10. FIELD AND POOL, OR WILDCAT Cato-Milnesand (San Andres)
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T8S-R30E
		12. COUNTY OR PARISH Chaves
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud, & Surf. Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

well spudded at 11:45 p.m., 11-11-67.

On 11-12-67 ran 8 jts. 8 5/8", 20' casing seated at 325'. Cemented with 200 sks Incor neat w/2% CaCl₂ & 1/4#/sk Flocele. Circulated 35 sks cement. Cement tests indicate 540 psi compressive strength in 12 hours @ 60°F. WOC 12 hours and tested 1000 psi for 30 minutes, o.k.

Note: Mr. J. W. Sutherland gave verbal permission on 11-6-67 to change surface casing program to 300' using 200 sks of cement.

RECEIVED

NOV 14 1967

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

J. E. Edison

TITLE Area Superintendent

DATE 11-13-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

J. W. Sutherland
District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.