

COUNTY	CHAVES	FIELD Wildcat	STATE NM
OPR	PAN AMERICAN PETROLEUM CORP.		
	1 Reid "B"		MAP
	Sec. 10, T-10-S, R-31-E		CO-ORD
	330' FSL, 1980' FWL of Sec.	30-005-20168	
	Spd 11-17-67	CLASS	E
	Cmp 4-11-68	FORMATION	DATUM
CSG & SX - TUBING			
13 3/8" 508' 300			
9 5/8" 4221' 850			
4 1/2" 11133' 1400			
LOGS EL GR RA IND HC A			
	TD 11150'		
PLUGGED & ABANDONED			

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT Cactus Drlg. Co. PROP DEPTH 11,000' TYPE RT
 DATE

F.R. 11-16-67; Elev. 4423' KB
 PD 11,000' - Mississippian
 Contr. - Cactus
 1-4-68 AMEND LEASE DESIGNATION: Formerly reported as
 Reid.
 11-20-67 Drlg. 1164'.
 11-27-67 Drlg. 3832'.
 Cored (Queen) 2864-2914', rec 48' anhy &
 red sd., w/NS.
 12-4-67 Drlg. 4364'.
 Cored 4055-4107', rec 52' being:
 18' anhy dolo., w/NS;
 34' anhy dolo., w/PPP, small scatt vuggs,
 fracs., fair-good bldg oil & gas.

12-4-67 Cont.
Cored 4107-35', rec 28' dolo., PPP, small
vuggs, bldg oil.
Cored 4135-88', rec 43' dolo., scatt PP to
vuggy poro., sli scatt bldg oil.
12-11-67 Drlg. 6330'.
12-18-67 Drlg. 7917'.
1-2-68 Drlg. 9521'.
DST 8955-9035', open 45 mins,
rec 60' very sli GCM,
1 hr ISIP 298#, FP 107-107#,
3 hr FSIP 795#.
1-8-68 Drlg. 10213'.
1-15-68 TD 10597', reaming.
Cored 10515-539', rec 24' sd & sh., w/NS.
Cored 10539-566', rec 27' sd & sh., w/NS.

1-22-68 Cored 10566-597', rec 31' sd & sh., w/NS.
TD 10906', prep core.
Cored 10628-655', rec 27' sd & sh., w/NS.
Cored 10770-782', rec 12' blk sh.
Cored 10900-906', rec 6' blk sh.
1-29-68 TD 11150', rng logs.
Cored 10906-932', rec 26' lm, sh & sd.,
w/good poro & odor in 9' sd.
Cored 10932-943', rec 7' sh & sdy sh.
DST 10845-943', open 1 hr 30 mins,
GTS 15 mins @ 600 MCFGPD increasing to
950 MCFGPD on 1" chk., SFP 80-23#,
Rec 350' GCM,
1 hr 30 min ISIP 3807#, FP 162-265#,
3 hr FSIP 3794#.

1-29-68 Cont.
DST 10932-11024', open 1 hr,
rec 270' Sli GCM,
1 hr 30 min ISIP 654#, FP 165-141#,
3 hr FSIP 885#.

2-5-68 TD 11150', prep to run casing.

2-12-68 TD 11150', PBD 11068', prep to test.
Perf 10918-924' W/2 SPF
Acid (10918-924') 1500 gals.
Swbd & Flwd 216 MCFGPD +54 BLW on 15 hr
test (10918-924')
Frac (10918-924') 60,000 gals brine +
30,000# sd.

2-19-68 TD 11150', PBD 11068', tstg.
Flwd 151 MCFGPD on 18 hr test thru 1"
chk., TP 20# (10918-924')

2-26-68 TD 11150', PBD 4196', swbg.
Sqd 10918-924' W/75 sx.
Set CI BP @ 4200', PB to 4196'
Perf 4093-97', 4108-10', 4119-24', 4126-29'
W/2 SPF
Acid (4093-4129') 1000 gals.
Swbd 9 BLW + 13 BFW in 10 hrs.
Swbd 100% wtr (4093-4129')

3-4-68 TD 11150', PBD 4196', tstg.
Perf @ 4169' W/4 SPI
Swbd 15 BLW in 1 hr (4169')
Att. to squeeze perfs 4093-4169'; Failed
Perf 4084-4130'
Acid (4084-4130') 500 gals.
Swbd 24 BLW in 1 hr 30 mins

3-11-68 TD 11150', PBD 4196', SI Tracer Survey
Swbd 4 BLW + 17 BFW w/tr. oil in 8 hrs
(4084-4130')
Acid (4084-4130') 1500 gals.
Swbd 7 BLWPH (4084-4130')
Acid (4084-4130') 6000 gals.
Swbd 200 BLW w/tr. oil in 18 hrs (4084-4130')
Swbd 61 BFW in 10 hrs (4084-4130')

3-18-68 TD 11150', PBD 4150', RU Pump
Set Retainer @ 4150'
Sqzd perf @ 4169' W/25 sx.
Swbd 35 BW w/tr oil in 9 hrs 30 mins.

3-25-68 TD 11150', PBD 4150', TOP
Pmpd 303 BFW w/tr. oil in 72 hrs.

4-1-68 TD 11150', PBD 4150', TOP
Pmpd 233 BW w/tr. oil in 72 hrs.

4-8-68 TD 11150', PBD 4150', TOP
Pmpd 248 BFW w/tr. oil in 72 hrs.

4-15-68 TD 11150', PBD 4150', PLUGGED & ABANDONED
Pmpd 81 BFW w/tr. oil in 24 hrs (4084-4130')
LOG: Anhy 1509', Yates 2166', Queen 2957',
SA 3398', Pi Zone 3946', Glorieta 4783',
Drinkard 6282', Abo 7180', Wolfcamp 8248',
Cisco 8755', Bough "C" 9053', Canyon 9282',
Strawn 9700', Atoka 10418', Mississippian
11082'.