

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 4649
7. Unit Agreement Name
8. Farm or Lease Name State "A"
9. Well No. 1
10. Field and Pool, or Wildcat Cato San Andres
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator Stevens Operating Corporation
Address of Operator P. O. Box 2408, Roswell, New Mexico 88201
Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 32 TOWNSHIP 8S RANGE 30E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

4137' GL, 4148' KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Set cast iron bridge plug @ 3350' w/35' sxs Class "C" w/2% CaCl₂ cement plug on top (perfs @ 3381'; 3390-92'; 3398'; 3402'; 3406-08').
- 2) Shoot 4½" casing @ 1500± and salvage casing.
- 3) Load hole w/9#/gal. mud and spot 100' Class "C" w/2% CaCl₂ cement plug @ 1550-1450' (50' inside 4½" casing and 50' above stub).
- 4) Spot 100' Class "C" w/2% CaCl₂ cement plug @ 1100-1000' (top salt @ 1050').
- 5) Spot 100' Class "C" w/2% CaCl₂ cement plug @ 350-250' (8 5/8" casing @ 303').
- 6) Spot 20' cement plug @ surface, cap well and install dry hole marker. There are no additional productive horizons in this well; no casing leaks or collapsed pipe.

THIS NOTICE IS NOTED 24
HOURS AFTER THE FILING OF
THIS NOTICE FOR THE C-103
TODAY, APRIL 19, 1983.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Controller DATE April 19, 1983

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE APR 21 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 20 1983

C.C.D.
HOBBY OFFICE