

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

DEC 6 1967

ANTHONY, CALIFORNIA

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
6. State Oil & Gas Lease No. K-3559
7. Unit Agreement Name
8. Farm or Lease Name Atlantic State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator Sunray DX Oil Company
3. Address of Operator P. O. Box 1416 - Roswell, New Mexico
4. Location of Well UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 10-S RANGE 30-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4098 D.F.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled 7-7/8" hole to TD of 3800'.
2. Ran open logs, Laterolog, Microlaterolog, Formation Density, GR-Sonic, and Sidewall Neutron. Log interpretation indicates no commercial quantities of oil or gas present.
3. Will lay cement plugs as follows:

100 sxs	3800' - 3480' (Cover H & J porosity zones)
25 sxs	2895' - 2825' (Cover top of San Andres)
25 sxs	1655' - 1585' (Cover top of Yates)
25 sxs	1110' - 1040' (Cover top of Rustler)
25 sxs	358' - 288' (In and out of base of 8-5/8")
10 sxs	At surface
4. Install dry hole marker and clear location.

NOTE: (Verbal approval obtained 12-4-67)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John Hastings

TITLE District Engineer

DATE 12-5-67

APPROVED BY John W. Runyan

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: