

NMOCC - ARTESIA
NMOCC - HOBBS
BLM - SANTA FE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42 P1421

SUNDAY NOTICES AND REPORTS ON WELLS

5. LEASE DESIGNATION AND SERIAL NO.
NM-0354427-F
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660 FNL * 1980 FWL Sec. 22 (Unit C, NE 1/4 NW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4162' R. D. B.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CROSBY "C" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

CATO SAN ANDRES

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

22-8-30 NMPM

12. COUNTY OR PARISH 13. STATE

CHAVES N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Completion

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On 10/9/67, 4 1/2" OD 9.5# J-55 Casing was set @ 3625 (TD) w/ 300 sq. in. or less. Tested casing w/ 2100 psi for 30 minutes. Test O.K. Perforated intervals 3450-53, 56-91, 3516-36, 47-50, 52-57, 60-64 w/ 2 ISPF. Acidized w/ 6000 gal 20%. Evaluated.

PT. Swab 60 BOX 73 BLW 24 hours. GOR 321, Cy 26.1° 19 MCFG.

TD - 3625
PBD - 3605
TPAY - 3450
SAN ANDRES

Comp - 10-14-67

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE AREA SUPERINTENDENT

DATE 10-16-67

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

014- USGS- ROS
F NSW
1- SUSP
F RRY

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

J. W. Luthman
District Engineer

RECEIVED

OCT 17 1967

U. S. GEOLOGICAL SURVEY
BOSTWELL, NEW MEXICO