

Form 9-331
(May 1963)
NM000 - ARTESIA
NM000 - HOBBS
BLM - SANTA FE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

DE-
re-

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 0155494-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Winkler Federal

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Cato

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

29-T8S-R30E

12. COUNTY OR PARISH
Chaves

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

SINCLAIR OIL & GAS COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 1920, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Spud, Run surf. casing, cement & test ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-27-67 Spud 12-1/4" hole @ 1:45 PM on 12-27-67 and drilled surface & red bed to 276'. Ran 8-5/8" OD 20# SP-40 casing set @ 276' and cemented w/200 sks. Incor Class C plus 1/4# Flocele per. sk. slurry wt. 14.8#. Cement Circulated.
12-28-67 Pressure tested casing to 800# for 30 mins. Tested O.K. WCC 24 hrs.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Superintendent

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

USGS Roswell, cc: Regional Office, cc; file

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO