

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT  
(Other side)TRIPL  
actions

re-

Form approved.  
Budget Bureau No. 42-R1424.

NMOCC - ARTESIA

NMOCC - HOBBS

BLM - SANTA FE

## SUMMARY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0155494 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Winkler Federal

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Cato San Andres

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA  
29-T8S-R30E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

SINCLAIR OIL &amp; GAS COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 1920, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

1980' fr the South line and West lines

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud, set surf. csg. cement & ☒ test.REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.) \*12-13-67 Spudded 12-1/4" hole 11:30 AM 12-13-67 and drilled surface and red bed  
to 285'. Ran 8-5/8"OD 20# SP-40 casing set @ 285' and cemented w/200 sks.  
Incor Class C plus 2% Ca. Chl. plus 1/4#Flocele per. sk. Slurry Wt. 14.4#  
Cement Circulated to surface. WOC 24 hrs.

12-14-67 Pressure tested casing to 800# for 30 mins. Tested O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

12-15-67

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

Dated

Orig&amp;4cc: USGS Roswell, N.M. cc: Reginal Office, cc: file

U.S. GEOLOGICAL SURVEY  
ROSWELL, N.M.