

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Shelf Off Company

3. ADDRESS OF OPERATOR
P. O. Box 991, Houston, TX 77001

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
660' FSL and 1980' FWL

AT SURFACE: Same
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
AM 0155254A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Anco Federal

9. WELL NO.
12

10. FIELD OR WILDCAT NAME
Cato (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 33, T6S, R30E

12. COUNTY OR PARISH Chaves 13. STATE
New Mexico

14. API NO.
NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4133' OF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JAN 18 1980

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 8-4-79: Pulled production equipment. Set CIBP @ 3300' and capped with 4 sx cmt. Loaded csg w/gelled brine wtr. csg free to 2250', cut off csg.
- 9-5-79: Ran 2 3/8" tbg and ppd 200 sx cmt plug. Pld tbg & pld csg to 1050'. Ppd 100 sx cmt plug. Pld csg to 315'. Ppd 50 sx cmt plug & pld csg. Set 10 sx cmt plug at surface of 6 5/8" csg and cut off wellhead. Marked location with Anco Federal No. 12, 660' FSL and 1980' FWL of Sec. 33, T6S, R30E, welded into 4" pipe set 4' above CR level. Cleaned location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. J. Fore TITLE Sr. Engr. Techn. DATE January 14, 1980

(This space for Federal or State office use)

APPROVED BY GEORGE H. STEWART TITLE _____ DATE MAR 13 1980

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

RECEIVED

MAR 5 1980

U.S. DEPARTMENT OF THE INTERIOR

RECEIVED

MAR 6 1980

G. C. D.
MINE & RECLAMATION OFFICE