

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-0155254A
2. NAME OF OPERATOR Shell Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1509, Midland, Texas 79702		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' ESL and 1080' FWL		8. FARM OR LEASE NAME Amco Federal
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4133 DF	9. WELL NO. 12
		10. FIELD AND POOL, OR WILDCAT Cato San Andres
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 33, T-8-S R-30-E, NMPM
		12. COUNTY OR PARISH Chaves
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-4-77 to 1-10-77

1. Pulled tubing.
2. Set cement retainer at 3300'. Pumped 300 sx Class C Cement and 250 sx FixSet Class C cement to squeeze perforation 3402-3478. Drilled out cement, to new PBTD 3425'. Pressure tested squeeze to 500 psi, held ok.
3. Perforated at 3384, 3386, 3394, 3396, 3402, 3407, 3408, 3410, 3412, 3417 (10 holes).
4. Acidized perforations 3384-3417 with 2000 gal 15% HCl.
5. Ran 107 its 2 3/8" tubing and hung at 3423'. Ran rods and pump. Placed on production.

RECEIVED

MAR 14 1977

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *G. W. Tullos*

TITLE *G. W. Tullos*
Senior Production Engineer DATE *3-11-77*

(This space for Federal or State office use)

APPROVED BY *J. S. Lara*
CONDITIONS OF APPROVAL IF ANY:

TITLE *ACTING DISTRICT ENGINEER*

DATE *MAR 16 1977*

RECEIVED

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are non-applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 660-379

RECEIVED

MAR 21 1977

OIL CONSERVATION COMM.
HOBBS, N. M.

U.S. OIL
CONSERVATION OFFICE

MAR 17 1977

RECEIVED