

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.NM000 - ARIZONA
NM000 - ILLINOIS
BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Shell Oil Company (Western Division)	8. FARM OR LEASE NAME Amco Federal
3. ADDRESS OF OPERATOR Post Office Box 1509, Midland, Texas 79701	9. WELL NO. 12
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FWL, Section 33, T-8-S, R-30-E, NMFM Survey, Chaves County, New Mexico	10. FIELD AND POOL, OR WILDCAT Gato (San Andres)
11. PERMIT NO.	12. COUNTY OR PARISH Chaves
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4133' DF	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing and Cement Test

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 2:15 PM, CST, 1-2-68.

Cemented 8 joints (252.68') 8 5/8", 24#, J-55, 8rd, new, ST&C, CP&I casing at 263' with 200 sacks Class "C" cement + 2% CaCl₂. Cement circulated. Plug down at 8:10 PM, CST, 1-2-68. WOC 12 1/4 hours. Tested casing to 1000 psi for 30 minutes, no pressure drop.

OPTION 2:

1. 236 cu. ft.
2. 200 sacks Class "C" + 2% CaCl₂
3. 60°F
4. 63°F
5. 500 psi
6. 12 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED BY D. L. LillyTITLE Division Mechanical Engineer DATE January 10, 1968

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

JAN 12 1968

ACCEPTED

District Engineer

U. S. GEOLOGICAL SURVEY
*See Instructions on Reverse Side
SANTA FE, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.