Form 9-331 Dec. 1973

orm Approved. ⊕ --- Budget Bureau No. 42-R1424

UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 0155254-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1. oil gas other	Amco A Federal 9. WELL NO.
2. NAME OF OPERATOR	3 \$ \$ \$ \$ \$ \$ \$
Shell Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Cato (San Andres)
P. O. Box 1509; Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Section 4, T-9-S;
below.) AT SURFACE: 660' FNL & 660' FEL	R-30-E, NMPM 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	Chaves New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	# []
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
CHARGE TO A LEROCULA TO CHARGE VIEW DEPORT OF	4098' GR: 공유성 등 유명 중
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	· 기업
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING MULTIPLE COMPLETE	change on Form 9–330.)
CHANGE ZONES	
ABANDON* \overline{\overli	5000
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	lirectionally drilled, give subsurface ocations and o
1. Pull prod equipment	# 10 W L
2. Spot 20 sx cmt @ TD.	scg.
3. Cut 4 1/2" csg from as deep as possible.	English English
4. Spot 100 sx cmt @ stub before pulling out	scg.
5. Spot 100 sx cmt above top of salt @ 1040'	Action of the state of the stat
6. Spot 50 sx cmt from 320' upward.	
7. Spot cmt in 8 5/8" @ surface from btm of	cellar down 20
8. Mark location w/4" OD steel pipe @ least	
Federal A No. 3, Sec. 4-9S-30E" welded on	r pipe. Assets pro Range
9. Clean location.	
Subsurface Safety Valve: Manu. and Type	Ft.
18. I hereby certify that the foregoing is true and correct W. Tullos	
SIGNED J. W. Tulla TITLE Senior Prod.	Eng. DATE 6-26-78
APPROVED BY APPROVED BY APPROVED BY	
	NGINEERATE AUG 1 7 1978
CONDITIONS OF APPROVAL, IF ANY	
	58\$p

O. C. C. ARTESIA, OFFICE

876f 8 1 aUA

SECEINED

AUG 1 8 1978