

N. P. O. C. C. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Shell Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 1509; Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL AND 660' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☒ ☐
(other) ☐

5. LEASE
NM 022636
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Hodge B Federal
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Cato (San Andres)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 34, T-8-S, R-30-E, NMPM
12. COUNTY OR PARISH Chaves 13. STATE New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4129' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Pull prod equipment
2. Spot 20 sx cmt @ TD.
3. Fill the hole w/salt gel mud consisting of 10# brine w/25# of gel/bbl.
4. Cut 4 1/2" csg from as deep as possible.
5. Spot 100 sx cmt @ stub before pulling out csg.
6. Spot 100 sx cmt above top of the salt @ 1090'.
7. Spot 50 sx cmt from 330' upward. Top of cmt must be 50' up inside 8 5/8" csg.
8. Spot cmt in 8 5/8" csg @ surf from btm of collar down 20'.
9. Mark location w/4" OD steel pipe at least 4' above GL w/"Shell Hodges B Federal No. 3, Sec. 34-8S-30E" welded on pipe.
10. Clean location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. W. Tullos TITLE G. W. Tullos DATE 6-27-78
Senior Prod. Eng.

APPROVED BY [Signature] TITLE ACTING DISTRICT ENGINEER DATE AUG 17 1978
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

AUG 18 1978

U.S. CONSERVATION COMM.
FEDERAL BUREAU OF INVESTIGATION

D.C.C.
ARTESIA, OFFICE

AUG 18 1978

RECEIVED