

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	SHELL OIL COMPANY				MAP
	1 Shell-Andrews Federal				
	Sec. 24, T-8-S, R-31-E				CO-ORD
	2080' FNL, 660' FEL of Sec.				30-005-20231
	Spd 2-17-68				
	Cmp 4-8-68				
	FORMATION		DATUM		CLASS
CSG & SX - TUBING					
9 5/8" 427' 250					
4 1/2" 4199' 425					
LOGS EL GR RA IND HC A					
	TD 4200'				
TEMPORARILY ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 4200' TYPE RT

F.R. 2-22-68
PD 4200' - SA
2-29-68 AMEND TO ADD REFERENCE NUMBER
2-26-68 TD 4200', prep to circ.
3-4-68 TD 4200', PBD 4165', SI.
Perf 4026-54' w/9 shots
Acid (4026-54') 4000 gals.
Swbd load & Swbd 118 BFW in 8 hrs (4026-54')
3-11-68 TD 4200', PBD 4070', SI.
Sqzd 4026-54' w/125 sx.
Perf @ 4026', 4031', 4033', 4037', 4040',
4046', 4048' w/1 SPI
Acid (4026-48') 3000 gals.
Swbd 97 BLW + 103 BFW in 17 hrs (4026-48')

3-18-68 TD 4200', PED 4070', SI.
Sqzd 4026-48' W/215 sx.
Perf @ 4025', 4026', 4031', 4033', 4037',
4038', 4040' W/1 SPI
Acid (4025-40') 2000 gals.
Swbd 74 BLW. + 98 BFW in 16 hrs (4025-40')
3-25-68 TD 4200', PBD 4070', SI.
4-1-68 TD 4200', PED 4070', prep to P&A.
4-8-68 TD 4200', PED 4070', TEMPORARILY ABANDONED
(Will plug at a later date)
LOG: Base Red Beds 1576' (+ 2825'), Yates
2100', SA 3300', SA Marker 3854', Slaughter
"A" 4008', Slaughter "B-C" 4092'.