

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved,
Budget Bureau No. 42-74424.

NMDCG - ARTECH

NMDCG - ARTECH

BLM - SUNDRA

SUNDRA NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

JUL 3 11 36 AM '68

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. NM-0557567
2. NAME OF OPERATOR Sun Oil Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 2792, Odessa, Texas 79760	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from South line & 660' from East line of Sec. 30, T11S, R31E.	8. FARM OR LEASE NAME Richardson-Federal
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 4142' Gr.	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T11S, R31E, N.M.P.M.
	12. COUNTY OR PARISH Chaves
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Preparing to abandon. 6-30-68 Procedure approved by Mr. Sutherland, U.S.G.S.

Dowell will plug with 25 sk incor cement ^{4200'} 42-4300', 25 sk Incor 2900-3000', 25 sk Incor 2350-2450', 25 sk Incor 1650-1750', 25 sks 400-500 in and out of 8 5/8" casing. Set 10 sk Incor plug - surface-40'. Cement steel marker(location).Formation Tops

Yates 1756'

Queens 2472'

San Andres 3030' (No porosity)

Glorietta 4300'

18. I hereby certify that the foregoing is true and correct

SIGNED

J. E. Edison

(This space for Federal or State office use)

TITLE

Area Superintendent

DATE

7-1-68

APPROVED BY

APPROVED

APPROVAL, IF ANY:

TITLE

DATE

JUL 2 1968

JUL 2 1968

J. W. SUTHERLAND
DISTRICT ENGINEER

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
LAS VEGAS, NEW MEXICO