

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions
verse side)

NMOC - ARTESIA
NMOC - NEEDS
BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals)

5. LEASE DESIGNATION AND SERIAL NO.

NM 027395

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pubco "33" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-8-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Chaves

N. M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Pennzoil United, Inc.

3. ADDRESS OF OPERATOR

P. O. Drawer 1828 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

810 FSL & 1980 FEL of Section 33, T-8-S, R-31-E,
Chaves County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4258 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Squeeze & recomplete as Gas Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-23-68 Ran Cement retainer on 2 3/8" tbg. & set @ 10,484'. - Sq. pfs. @ 10,586' w/125 sx Class "H" cement w/1% CFR-2. Obtained 5000 psi - sq. w/65 sx cement in formation. R.O. remaining cement and pulled tbg.

9-24-68 Perforate 1 hole per foot 8508' to 8516'. Ran tbg. & pkr

9-25-68 Displace hole w/oil and spot 500 gals mud acid - Break down pfs. 8508-8516'. Well flwd after treatment

9-26-68 Retreat pfs. 8508-8516' w/5,000 gals retarded acid. Swbd & kick off well. Flow to clean up acid water.

RECEIVED

OCT 8 1968

U.S. GEOLOGICAL SURVEY
COWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Adrian C. Boyd

TITLE

Petroleum Engineer

DATE

10-4-68

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

J. W. Southland
District Engineer

*See Instructions on Reverse Side