

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.NMOCC - ARIZONA
NMOCC - MEXICO
BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

M-022636

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hodges Park "A"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cato (San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 27, T-8-S, R-30-E

NMPM

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

The Eastland Drilling Company

3. ADDRESS OF OPERATOR

730 Petroleum Life Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

330' FWL and 990' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4171' RT

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒ Casing settingREPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded w/11" bit at 800 3:00 p.m. August 20, 1968 and drilled to 395' in redbed. Run 12 joints #2, 24#, J-35, 8-5/8" casing set at 393.50'. Cemented with 275 sacks regular cement with 2% calcium chloride. Circulated approximately 75 sacks excess cement. Cement in place at 9:00 a.m., August 21, 1968. Allowed casing to set for 12 hours. Released pressure and nipped up. Drilled cement plug at 5:00 a.m., August 22, 1968, after testing casing with 1000 psi for 30 minutes. No pressure leakoff.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE SuperintendentDATE August 23, 1968

(This space for Federal or State official use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

District Engineer

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.