

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

NM200 - SANTA FE
NM200 - SANTA FE
BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

5. LEASE DESIGNATION AND SERIAL NO.

NM-022636

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hodges Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cato (San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

**Sec. 23, T-8-S, R-30-E,
NMPH**

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

The Eastland Drilling Company

3. ADDRESS OF OPERATOR

730 Petroleum Life Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2305' from South line and 2310' from East line.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4,214' RT

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **Casing setting**

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded w/11" bit at 12:30 p.m. Sept. 3, 1968 and drilled to 389' in redbed. Ran 14 joints #2, 24#, J-55, 8-5/8" casing, 375.70' set @ 388.20'. Cemented w/250 sacks regular cement with 2@ Caelz. Circulated approximately 70 sacks excess cement. Cement was in place at 7:00 a.m. Sept. 4, 1968. Allowed casing to set for 12 hours. Released pressure and nipples up. Tested casing with 1000 psi for 30 min. with no pressure leakoff. Drilled cement plug at 1:00 a.m. Sept. 5, 1968.

RECEIVED

SEP 18 1968

18. I hereby certify that the foregoing is true and correct

SIGNED

Lu. Gawn

TITLE **Secretary**

DATE **Sept. 17, 1968**

(This space for Federal or State (CL) use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

J. W. ...
District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.