NO. OF COPIES RECEIVED			Form C-103
DISTRIBUTION			Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CONS	SERVATION COMMISSION	Effective 1-1-65
FILE		er er	
U.S.G.S.		, 100	5a. Indicate Type of Lease
LAND OFFICE	er er	Company Contracting	State X Fee
OPERATOR			5, State Oil & Gas Lease No.
			OG -2273
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
OIL X GAS WELL	OTHER-		7, Unit Agreement Name
2. Name of Operator			8. Farm or Lease Name
Chambers & Kennedy			Arco State
3, Address of Operator			9. Well No.
607 Midland National Bank Bldg., Midland, Texas 79701			1
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER J 2310 ' FEET FROM THESOUTHLINE AND 1980 ' FEET FROM			Chaveroo
THE East LINE, SECTION 4 TOWNSHIP 8-S RANGE 33-E NMPM.			
15. Elevation (Show whether DF, RT, GR, etc.)			12, County
4418'			Chaves
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
	Appropriate Box to indicate r	·-	THE DATA
\Box			ALTERING CASING
PERFORM REMEDIAL WORK	PLUG AND ASANDON	REMEDIAL WORK	PLUG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING		OTHER	
Set Surface Csg. X			
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed			
17. Describe Proposed or Completed Opwork) SEE RULE'1103.	perations (Clearly state all pertinent ael	aits, and give pertinent dates, includin	ig estimated date of starting any proposed
Spud date 10/25/68	@ 1:00 P.M.		
Set 374' of 8-5/8" 20# csg. Cement w/250 sacks of Lone Star Incor Class C			
2% Ca Cl ₂ 1/4# D-29 Slurry Wt. 14.8 (8 hr 2200 psi, 12 hr - 3000 psi.)			
Cement allowed to set 15 hours before testing with 1000# for 30 minutes.			
_			
Test O.K. (Cement	Circulated to surre		
	6 0 /4 11 1 2 2 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2		Sat 44501 of
Propose to drill a 6-3/4" hole to approximately 4500' T.D. Set 4450' of			
4-1/2" 9.5# csg. w/	250 sx. cement.		
	250 511. 00		
		•	
		•	
18. I hereby certify that the information	above is true and complete to the best	of my knowledge and belief.	
18. I hereby certify that the information	above is true and complete to the best		
18. I hereby certify that the information	above is true and complete to the best	of my knowledge and belief. gr. of Production	11/1/68
18. I hereby certify that the information	above is true and complete to the best		11/1/68
18. I hereby certify that the information	above is true and complete to the best	gr. of Production	11/1/68
18. I hereby certify that the information SIGNED STORY APPROVED BY APPROVED BY	above is true and complete to the best		DATE