

N. M. O. C. C. CC
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)TS
reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE IDENTIFICATION AND SERIAL NO.

NM 027348

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR H. L. BROWN, JR.		7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR 309 MIDLAND TOWER, MIDLAND, TEXAS		8. FARM OR LEASE NAME SHELL 20 FEDERAL
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL 1980' FWL SEC. 29, T-8-S, R-31-E		9. WELL NO. 1
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT WILDCAT
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4198.3 GL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 29, T8S, R31E
		12. COUNTY OR PARISH CHAVES
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-9-68: Moved in rig. Spudded @ 3:15 PM. Drilled to 264' in redbed. Slope 1/4 deg. @ 250'. Ran 7 joints of 8-5/8" 20# csg. set at 264'. Cemented w/250 sx Incon w/2% CaCl₂. EM Plug down @ 6:45 PM 12-8-68. Cement circulated.

12-16-68: Logged from 4:15 AM to 4:45 PM. Ran 118 joints of 4-1/2" 9-1/2#, 10-1/2#, 11.6# csg set at 3818'. Corrected TO to 3818 to Schlumberger measurement. Cemented w/250 sx Incon. Plugged down at 3:45 AM 12-16-68. Set slips and nipped up. Rig released at 7:00 PM.

RECEIVED

MAR 24 1969

MAR 20 1969

18. I hereby certify that the foregoing is true and correct

SIGNED

C. L. Leonard

TITLE

PRODUCTION CLERK

DATE

3-18-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

MAR 20 1969

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.