

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG-2273	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Chambers & Kennedy		8. Farm or Lease Name Arco State
3. Address of Operator 607 Midland National Bank Bldg., Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER 0 , 1980 FEET FROM THE East LINE AND 990 FEET FROM THE South LINE, SECTION 4 , TOWNSHIP 8-S , RANGE 33-E NMPM.		10. Field and Pool, or Wildcat Chaveroo
15. Elevation (Show whether DF, RT, GR, etc.) 4420 Gr		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 22, 1969
Ran 140 jts (4,424.50') 4½" OD 9.50# J55 ST&C Condition B csg and set @4436'.
Ran HOWCO oil and caps, HOWCO cement, float shoe, HOWCO latchdown baffle assembly
on top of 8' shoe joint. Cemented w/375sx Class C 5050 poz w/8# salt per sack.
Plugged w/1700 psi. Released pressure to zero. Plug held okay. Ran temperature
survey. Top of cement 3380'.

Cop to 1

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u><i>Joe Thompson</i></u>	TITLE <u>Manager of Production</u>	DATE <u>3/28/69</u>
APPROVED BY <u><i>Joe Thompson</i></u>	TITLE <u>SUPERVISOR DISTRICT 1</u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		