

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 9 2 20 PM '69

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-8638

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Chambers & Kennedy	8. Farm or Lease Name Champlin State
3. Address of Operator 607 Midland Nat'l. Bk. Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER N , 1980 FEET FROM THE West LINE AND 660 FEET FROM THE South LINE, SECTION 4 TOWNSHIP 8-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat Chaveroo
15. Elevation (Show whether DF, RT, GR, etc.) 4427' Gr.	12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Surface Casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12½" hole @9:45 P.M. July 1, 1969.

Drill 365' - 12½" hole - Dev. ¼°.

Set 363' - 8 5/8" 20# csg; cemented w/250 sx - Class "C" 2% Ca Cl₂. Slurry Wt. 14.8#. Circulated approximately 30 sx cement. Wait on cement 12 hrs. Test casing 1000# 30 min - OK.

Propose to drill a 7-7/8" hole to approximately 4150', then reduce to 6-3/4" hole and drill to approximately 4450'. Will set 4-1/2" 9.5# casing at total depth and cement w/250 sx cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>G. C. Thompson</i></u>	TITLE <u>G. C. Thompson</u> <u>Manager of Production</u>	DATE <u>July 7, 1969</u>
APPROVED BY <u><i>[Signature]</i></u>	TITLE <u>VISOR DISTRICT</u>	DATE <u>JUL 10 1969</u>
CONDITIONS OF APPROVAL, IF ANY:		