

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

**MT-022636**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

**Hodges Federal**

9. WELL NO.

**3**

10. FIELD AND POOL, OR WILDCAT

**Cato (San Andres)**11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA**Sec. 27, T-8-S, R-30-E****NMPM**

12. COUNTY OR PARISH

**Chaves**

13. STATE

**New Mexico**

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

**The Eastland Drilling Company**

3. ADDRESS OF OPERATOR

**704 Petroleum Life Building, Midland, Texas 79701**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface**1980' from North and East lines**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

**4171' GR, 4182' KDB**

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐**Casing Setting** ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 11" hole at 7:00 p.m., October 15, 1969, and drilled to 388 feet in red bed. Ran 12 joints 32#, J-55, 8-5/8" casing, 372 feet set at 385 feet. Cemented with 200 sacks reg. 2% CaCl<sub>2</sub>. Cement was in place at 10:00 a.m. October 16, 1969. Circulated out approximately 35 sacks excess cement. Allowed casing to set 12 hours. Wipped up and tested casing with 1000 psi for 30 minutes with no pressure leak-off. Drilled cement plug at 5 a.m., October 17, 1969.

RECEIVED

OCT 23 1969

OCT 24 1969

O. C. C.  
ARTESIA, OFFICERECEIVED  
OCT 23 1969  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

**Superintendent**

DATE

**10-30-69**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

ACCEPTED FOR RECORD  
OCT 23 1969  
Date  
ACTING  
District Engineer

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.