

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0240993

6. IF INDIAN, ALLOTTEE OR TRIBAL NAME

MAR 9 1970

7. UNIT AGREEMENT NAME

North King Camp Unit

8. FARM OR LEASE NAME

North King Camp Unit

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31-T13S-R30E

12. COUNTY OR PARISH

13. STATE

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Jack L. McClellan

3. ADDRESS OF OPERATOR

Box 848, Roswell N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3763'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to pull 7" casing used to shut off invading water, and plug and abandon well placing a 100 sack cement plug from 1850' to 1550', a 30 sack cement plug at base of Salt from 1100' to 1000', a 30 sack plug $\frac{1}{2}$ in and $\frac{1}{2}$ out of 8 5/8" surface casing from 550' from 550 to 450'. Will place a 10 sack cement plug in 8 5/8" casing at surface and install dry hole marker.

Note: Verbal approval from Mr. Beekman 2-24-70 on above outlined operation.

RECEIVED

MAR 6 1970

O. C. C.
ARTESIA, OFFICE

RECEIVED

MAR 6 1970

GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the above is true and correct

SIGNED

Alno Milford

TITLE Production Supt.

DATE 2-24-70

(This space for Federal or State comment)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

W. L. BECKMAN

*See Instructions on Reverse Side