

N. M. O. C. C. COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
SUBMIT IN TRIPLICATE\*  
(Other instructions on  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0109856-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holbeck Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T. R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 9, T14S, R30E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ WELL GAS ☐ WELL OTHER ☐ Wildcat
2. NAME OF OPERATOR  
McGrath & Smith, Inc.
3. ADDRESS OF OPERATOR  
418 Building of the Southwest, Midland, Texas 79701
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
660' FNL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 3843 KB 3850

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cementing 8 5/8 casing.

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 11" hole at 3:30 p.m., 6-25-70.

Drilled 11" hole to 355'.

Cemented 8 5/8 - 8rd - 20# - used casing at 354' with 75 sx. TLW 105% water.

followed by 75 sx. Class C 2% CACL<sub>2</sub>. Plug down 3:30 a.m., 6-26-70.

10 sx cement. WOC 18 hrs. Tested 8 5/8 to 400 psi - OK.

RECEIVED

JUL 16 1970

O. C. C.  
ARTESIA, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Sup't.

DATE

7-13-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES  
JUL 15 1970  
Date  
ACTING District Engineer

\*See Instructions on Reverse Side