

INMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Dalport Oil Corp.	8. FARM OR LEASE NAME Stringer-Federal
3. ADDRESS OF OPERATOR 3471 First National Bank Bldg., Dallas, Tx	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 600' PS & WL	10. FIELD AND POOL, OR WILDCAT Southeast Chaves Queen
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 17-12S-31E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4094 KB	12. COUNTY OR PARISH Chaves
	13. STATE N.M.

RECEIVED

MAR 14 1978

O. C. C.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other) <u>Run tubing - clean out</u>	☒		☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Original info: PBD 2576, perforations 2535-52

- 2-27-78 Removed Halliburton casinghead. Put on new Larkin 4-1/2" X 2-3/8" head. Loaded hole with fresh water. Ran used 2-3/8" tubing. Top frac sand at 2447 g.m. Could not wash out. 119' of fill up. SI.
- 2-28-78 Pulled tubing and gas anchor. Ran 3-1/2" bit on bottom of tubing. Reversed fresh water down casing. Washed out to 2545 g.m. Lost circulation. Pulled tubing and bit. Ran tubing, tagged top sand at 2544 g.m. Total 82 joints in hole (2485.44') + 8' gas anchor, 3' perf. nipple, 1' seating nipple. Base anchor at 2497.44 g.m.
- 3-1-78 Swabbed once. Kicked off. Flowing gas.

RECEIVED

MAR 6- 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Geologist DATE 3-2-78

(This space for Federal or State office use)

APPROVED BY Lee D. Lara TITLE ACTING DISTRICT ENGINEER DATE MAR 13 1978

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.