

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER DRY HOLE 2. NAME OF OPERATOR AZTEC OIL & GAS COMPANY 3. ADDRESS OF OPERATOR P. O. BOX 837, HOBBS, NEW MEXICO 88240 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' S & 1980' E Section 31 - T-10S - R-30E 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4009.2 GL	5. LEASE DESIGNATION AND SERIAL NO. NM 0298103 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME FEDERAL "TS" 9. WELL NO. 1 10. FIELD AND POOL, OR WILDCAT WILDCAT 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 31-10S-30E NMPM 12. COUNTY OR PARISH Chaves 13. STATE N.M.
---	---

16. **Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data**

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) ☐	

(NOTE: Report results of multiple completion only on Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 11:00 A.M. 8-12-70. Drilled 325' - 12 1/4" hole.
Set 8 5/8", 24# casing at 311' with 225 sacks Encore cement.
Circulated back to surface. Pressure test to 1000# for 30 min. OK.
Drilled 7 7/8" hole to 3350'. Cored 3350' to 3450'. Ran Guard and Sidewall Neutron Log.
Ran DST 3352-3490'.
Plan to Plug well with four 100' plugs: 3350-3250', 2025-1925', 900-800' & 370-270'.
(Oral approval by Mr. Jim Knauf, USGS, Artesia, New Mexico.)
Set 5' Dry Hole marker with 10 sack cement plug, ~~2-28-70~~

RECEIVED
SEP - 3 1970
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED <u>ORIGINAL SIGNED BY</u> HARDY GRAYSON	TITLE <u>FIELD FOREMAN</u>	DATE <u>August 31, 1970</u>
(This space for Federal or State office use)		

APPROVED BY <u>CONDITIONS OF APPROVAL, IF ANY:</u>	TITLE _____	DATE _____
--	-------------	------------

APPROVED
SEP 2 1970
R. L. BEEKMAN
ACTING DISTRICT SUPERVISOR

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229
GPO 8 37-499
867-851

RECEIVED
OCT 22 1970
OIL CONSERVATION DIVISION
RECEIVED
OCT 22 1970
D. C. C.
ARTESIA, OFFICE