

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator S. P. Yates		8. Farm or Lease Name Phyllis Williams Fee
3. Address of Operator 207 South 4th Street - Artesia, New Mexico 88210		9. Well No. 1
4. Location of Well UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 13S RANGE 31E NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4138' GL		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER 5 1/2" csg., Perforate & Sand Frac <input checked="" type="checkbox"/>			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 11-13-70 - TD 2859, PBTD 2808' - Ran 2848' of 5 1/2" 15.5# 8R J-55 casing with guide shoe on bottom and insert float 1 jt off bottom, set at 2858' (KB depth) cemented w/200 sacks of Neat cement. P.D. 4:00 AM 11-13-70.
- 11-30-70 - Bailed hole to 1900'. Perforated by Perfojet with select fire jets (.42" dia) using radioactive pips for each perforation. Perforated as follows: 2711-14' (4 shots), 2697-99 (3 shots), 2693-95 (3 shots), 2685 1/2-88' (5 shots), 2680 1/2-83 (5 shots). Total 20 shots.
- 12-7-70 - Broke down formation with 2000 gallons 15% acid and swabbed well dry. Had show of oil and Sandfraced in 2 stages, by Dowell, using ball sealers, 1000 gallons mud acid, 57000 fresh water & 30000# 20-40 sand.

Electric Logs enclosed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Raymond Yates TITLE Engineer DATE 12-17-70

APPROVED BY [Signature] TITLE SECRETARY DATE 12-17-70

CONDITIONS OF APPROVAL, IF ANY:

Let 1000 ft. in new test & MCC time

RECEIVED

JUN 10 1970

OIL CONSERVATION DIST. DIV.
HOUSTON, TEXAS