

Form 431
(May 1968)

N. M. O. G. 101

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Bureau Order No. 42-81424.

5. LEASE DESIGNATION AND SERIAL NO.

NM0306974A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT ASSIGNMENT NAME

8. FARM OR LEASE NAME

Shell Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SUEVEY OR AREA

Sec. 23, T13S, R30E

12. COUNTY OR PARISH

Chaves

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Coquina Oil Corporation

3. ADDRESS OF OPERATOR

418 Bldg. of Southwest, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit D, 660' FNL and 660' FWL of Sec. 23

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

GL 3948

KB 3960

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded 4:30 p.m., 11-30-70. Cmt'd. 8 5/8 - 24# casing at 355' with 200 sx.
Drld. 7 7/8 hole to TD 2312'. Cored Queen 2250-2283'. P&A as follows:
25 sx. Class H cement plugs spotted as follows: 2172-2272', 1280-1380',
720-820', 275-355', and 10 sx. in top of 8 5/8. Capped well and erected
DHM. P&A complete 5:30 p.m., 12-8-70.

RECEIVED

DEC 10 1970

U. S. GEOLOGICAL SURVEY
ARTIFICIAL RECHARGE

18. I hereby certify that the foregoing is true and correct

SIGNED

J. B. Taylor

TITLE

Sup't.

DATE

12-9-70

(This space for Federal or State office use)

APPROVED BY

CONDITION OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

FEB 10 1971

*See Instructions on Reverse Side

RECEIVED

FEB 12 1971

OIL CONSERVATION COMM.
HOBBS, N. M.

O. E. C.
ARTESIA, OFFICE

FEB 11 1971

RECEIVED