

COUNTY CHAVES FIELD Cato STATE NM 30-005-20174

OPR GIENN PET. CORP. MAP

1 Sun - State CO-ORD

Sec 36, T-7-S, R-30-E

660' FNL, 660' FWL of Sec

Spd 4-26-71

Cmp 6-11-71

CSG & SX TUBING

8 5/8" at 272' w/300 sx

4 1/2" at 3720' w/200 sx

LOGS EL GR RA IND HC A

TD 3720'

IP (San Andres) Perfs 3553-3657' P 45 BOED + 8 BK. Pot based on 24 hr test. GOR 705; Grav 27.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Logging Service, Inc.

CONT. Ard PROP DEPTH 3750' TYPE R2
DATE

4-27-71 F.R. 4-6-71; Opr's Elev. 4215' KB
5-3-71 PD 3750' RE (San Andres)
5-10-71 Contractor - Ard
5-17-71 TD 275'; WOG
5-24-71 TD 3720'; Prep Log
TD 3720'; WOGU
TD 3720'; WOGU
TD 3720'; RUP
Perf @ 3642', 3652', 3655', 3657'
Acid (3642-57') 250 gals
Swbd dry (3642-57')
Acid (3642-57') 1000 gals

CHAVES
GLENN PET. CORP.

Cato NM
#1 Sun - State

Sec 36, T7S, R30E
Page #2

5-24-71

Continued

Swbd 5 BFPH (50% oil) (3642-57')

Perf @ 3553', 3555', 3569', 3575', 3603'

Swbd 5 BFPH (50% oil) (3642-57')

Acid (3553-3657') 1000 gals

Swbd 10-15 BFPH (50-60% oil) (3553-3657')

Acid (3553-3657') 2000 gals

6-1-71

TD 3720'; WO Electricity

6-14-71

TD 3720'; WO Pot

6-21-71

TD 3720'; COMPLETE

LOG TOPS: Anhydrite 1175', Yates 1632',
Seven Rivers 1734', Queen 2352', Grayburg
2370', San Andres 2780'

6-24-71

COMPLETION REPORTED