

R **REMOVED**

JUN 20 1972

ON GOVERNMENT WORK
ARTICLE 10, SECTION 1

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. Interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Strawn	9340	9380	Sand DST 9310-80, T.O. 2½ hrs. GTS 1'15" TSTM. Rec. 350' GCM & 15' XWCM. Pressures: 60" ISIP 2088, FP 134-164, 2½' FSIP 2149.	Yates	1420	
Atoka-Morrow	9490	9952	Sand. DST 9660-9756. T.O. 27". GTS 3". G.V. 4 MMCFC. Rec. 580' dist. & 150' HO& GCM, No water. Pressures: 60" ISIP 3318', FP 829- 1202', FSIP 3318'.	Queen	2142	
				San Andres	2762	
				Glorieta	4165	
				Abo	6425	
				Wolfcamp	7615	
				Strawn	8980	
				Atoka	9490	
				Morrow	9798	
				Miss.	10,125'	
				Woodford	10,598'	
				Devonian	10,666'	
Devonian	10,666'		Dolomite. DST 10,672-10,731' T.O. 2'. Rec. 5500' Sulf. Wtr. Pressures: 60" ISIP 4342, FP 359-2367, 120" FSIP 4361.			

RECEIVED
JUN 27 1972
S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO