

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator HUMBLE OIL & REFINING COMPANY	8. Farm or Lease Name NEW MEXICO "CR" STATE
3. Address of Operator P.O. BOX 1600, MIDLAND, TEXAS 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>NORTH</u> LINE AND <u>660</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>32</u> TOWNSHIP <u>9-S</u> RANGE <u>30-E</u> NMPM.	10. Field and Pool, or Wildcat UNDESIGNATED
15. Elevation (Show whether DF, RT, GR, etc.) TO BE FILED LATER	12. County CHAVES

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUDDED 12 1/4" HOLE AT 6:30 P.M., 4-3-72. DRILLED TO 1485', 4-4-72. RAN 36 JTS. 9 5/8" CSG, SET AT 1476'. CEMENTED W/400 SX CLASS C W/4% GEL AND 2% CACL. TAILED IN W/300 SX CLASS C W 2% CACL. MAX OIRC. PRESS 800 - BUMPED PLUG W/1100#. NIPPLED UP ON 9 5/8" CSC. TESTED BOP TO 300# + 2000#. TESTED FOR 30 MIN., Q. CEMENT CIRCULATED OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Joe D. Ramey</u>	TITLE <u>UNIT HEAD</u>	DATE <u>4-10-72</u>
APPROVED BY <u>Joe D. Ramey</u> Dist. 1, Supv.	TITLE _____	DATE <u>APR 12 1972</u>
CONDITIONS OF APPROVAL, IF ANY:		