

COUNTY CHAVES FIELD Wildcat STATE NM 30-005-20400

OPR HUMBLE OIL & REFG. CO. MAP

1 New Mexico "CR" State

Sec 32, T-9-S, R-30-E CO-ORD

1980' FNL, 660' FWL of Sec

Spd 4-2-72

CLASS

EL 40362

Cmp 5-21-72

FORMATION

DATUM

FORMATION

DATUM

CSG & SX TUBING

8 5/8" at 1476' w/700 sx

5 1/2" at 7434' w/1375 sx

LOGS EL GR RA IND HC A

TD 9450'; PBD 7391'

IP (Wolfcamp) Perfs 7266-90' F 216 BOPD + 7 BW. Pot based on
23 hr test thru 1/4" chk. GOR 1087; Grav 43.6; CP Pkr; TP 100#

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sharp #32
DATE

PROP DEPTH 9400' TYPE RT

F.R. 3-27-72; Opr's Elev. 4036' DF

PD 9400' RT (Morrow)

Contractor - Sharp #32

4-3-72

TD 1485'; Rng Casing

4-10-72

Drlg. 2460'

4-17-72

Drlg. 4920'

4-24-72

Drlg. 6400'

5-1-72

Drlg. 7945'

5-8-72

Drlg. 8495'

5-17-72

TD 9450'; Prep DST

5-24-72

TD 9450'; PBD 7391'; Prep Perf

DST 9235-9450', open 1 hr 10 mins, rec 270' DM,

1 hr ISIP 455#, FP 359-362#, 2 hr FSIP 506#

5-30-72

TD 9450'; PBD 7391'; COMPLETE

Perf 7266-90' w/1 SPF

Acid (7266-90') 6000 gals

CHAVES Wildcat NM Sec 32,T9S,R30E
HUMBLE OIL & REFG. CO. 1 New Mexico "CR" State Page #2

5-30-72

Continued

LOG TOPS: Rustler 847', Yates 1406',
San Andres 2640', Glorieta 4014', Tubb
5502', Abo Shale 6356', Wolfcamp 7188',
Canyon 8219', Strawn 8696', Morrow 8996'
Completed in Undesignated Wolfcamp Field.

6-3-72

COMPLETION REPORTED