(May 1963) <b>DEPA</b>	UNITEDISTATES	S. C. COPY  SUBMIT IN TRIPLICA  (Other instructions  (ERIOR verse side)	re- Budget Bureau No. 42-R1424.  5. LEASE DESIGNATION AND SERIAL NO.
GEOLOGICAL SURVEY			NM 0271104-A
(Do not use this form for Use "AP	NOTICES AND REPORT PROPOSALS to drill or to deepen or perfection for PERMIT—" for s	IS ON WELLS plug back to a different reservoir. uch proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.  OIL GAS WELL OTH  2. NAME OF OPERATOR	ier		7. UNIT AGREEMENT NAME
JACK L. MCCLELLA 3. ADDRESS OF OPERATOR	A N		8. FARM OR LEASE NAME  TOLPAT FEBERAL "A"  9. WELL NO.
P. O. Box 848, R	Roswell, New Mexic	:0 88201 <b></b>	= -
See also space 17 below.) At surface	tion clearly and in accordance with	any State requirements	10. FIELD AND POOL, OR WILDCAT WILDCAT
660' FS & WL		The Nature of Motice, Report, o	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
14. PERMIT NO.	15. ELEVATIONS (Show wheth	er DF, RT, CR, etc.) GEOLOGICAL MEN	SEC. 22-T10S-R30E  12. COUNTY OR PARISH 13. STATE  CHAVES NEW MEXIC
<sup>16.</sup> Check	k Appropriate Box To Indica	te Nature of Motice, Report, o	or Other Data
	INTENTION TO:	SUBS	SEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE ABANDON*	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT*
REPAIR WELL (Other)	CHANGE PLANS	(Other)(Note: Report rest	ults of multiple completion on Well mpletion Report and Log form.)
	ILLED TO A DEPTH	of 3650' and was t	
AS FOLLOWS: SET	100! CEMENT BLUC	c ** 08/10 00/101 (c	
			AN ANDRES), 1600-1700
(YATES), AND 270-	-3701 (IN AND OUT	of stub of 8-5/8"	AN ANDRES), 1600-1700'  CASING), WITH A 20'  THE LOCATION WILL BE
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER	of stub of 8-5/8"	casing), with a 20'
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER	of stub of 8-5/8"	casing), with a 20'
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER	of stub of 8-5/8"	casing), with a 20'
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER	of stub of 8-5/8"	casing), with a 20'
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER	of stub of 8-5/8"	casing), with a 20'
(YATES), AND 270- PLUG AT SURFACE.  CLEANED AND LEVEL  S. I hereby certify that the foregoin	-370' (IN AND OUT DRY HOLE MARKER LLED.	OF STUB OF 8-5/8" WILL BE ERECTED.	CASING), WITH A 20' THE LOCATION WILL BE
(YATES), AND 270-	-370' (IN AND OUT DRY HOLE MARKER LLED.  Ing is true and correct  Mac Clellantitle	of stub of 8-5/8"	casing), with a 20'

\*See Instructions on Reverse Side

ARTESIA, OFFICE