

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Federal NM 055564

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Isler-Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Many Gates - Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T-9-S, R-30-E

12. COUNTY OR PARISH 13. STATE

Chaves New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

Humble Oil & Refining Company

NOV 6 1972

3. ADDRESS OF OPERATOR

P. O. Box 1600, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 1,980' FSL & 660' FEL

RTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4,014 GR

4,027 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to depth of 7,330'.

Propose to plug & abandon as follows:

Plug No.	Sacks	Type	Plug From	To
1	35	Class "H"	7,250	7,150
2	40	Class "H"	3,998	3,898
3	40	Class "H"	3,300	3,200
4	40	Class "H"	2,180	2,080
5	35	Class "H"	1,547	1,447
6	10	Class "H"	34	4

4' below ground level. Clean pit; install dry hole marker; place 10.3# mud laden fluid between plugs. No casing to be pulled.

Verbal approval received from U.S.G.S. prior to actual P&A.

RECEIVED

NOV 2 1972

U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

D. L. Clemmer
D. L. Clemmer

TITLE

Proration Specialist

DATE

October 31, 1972

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
NOV 3 1972
H. L. BEEKMAN
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side