

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. U. C. COPY
SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-054926-A	
2. NAME OF OPERATOR Read & Stevens, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -	
3. ADDRESS OF OPERATOR P. O. Box 2126, Roswell, New Mexico 88201		7. UNIT AGREEMENT NAME -	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FEL Sec. 25, T-12-S, R-30-E, N.M.P.M.		8. FARM OR LEASE NAME Jackson	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4018 GR. - 4027.2 RKB		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25-12S-30E	
		12. COUNTY OR PARISH Chaves	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-19-73 Rigged up completion unit. Perforate by Welex using 3 1/2" Super Dyna Jet. Perf. 2-1/2" holes per foot, 2426'-34', 2440'-46', 2454'-62' RKB, total of 44 holes. Ran tubg. & pkr. Set pkr. @ 2284' and 2 3/8" tubg. @ 2473'. Acidized with 500 gals. 15% mud acid, break down @ 2200 PSI, aver. treating rate 3 bbls. per min., aver. treating press. 1900 PSI, ISDP 1500 PSI, 5 min. SIP 1500 PSI, total load 23 bbls. Open well and flowed back load in 30 min.

RECEIVED

FEB 15 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 2-5-73

(This space for Federal or State office use)

TITLE

DATE

APPROVALS OF APPROVAL, IF ANY:

APPROVED
FEB 16 1973
H. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side