	N. M. OIL CONS. COMMISSION P. O. BOX 1980 Hobbs, New Mexico 88240	,
(June 1990) DEPARTMEN	TED STATES IT OF THE INTERIOR LAND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires. March 31, 1993 5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		NM-0199827-A 6. If Iralian, Allottee or Tribe Natte
SUBMIT IN TRIPLICATE		7 If Unit or CA, Agreement Designation
1 Type of Well Out Gas Well Well Outer		SW 988 B Well Native and No
2 Name of Operator		Amerada Federal #1
Charles W. Hicks 3 Address and Telephone No.		9 API Well No 30-005-20457
1500 West Third Street, Roswell, New Mexico 88201 Phone 622-8063		10. Field and Pool, or Exploratory Area
+ Location of Well (Foolage, Sec., T., R., M., or Survey Description) Unit N		Vest Ranch Queen Assoc.
610' FSL & 2310' FWL Sec. 5, T15S, R30E NMPM		Chaves Co. New Mexico
CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intern	X Abandonment	Crishige of Plans
Subsequent Report	Plugging Back	Non-Koutire Fracturing
Final Abandonment Notice	Alterng Casing	L. Water Shut-Off Conversion to Injection
	Unter	Dispuse Water Nuce Report results of multiple complexion on write
	I pertinent details, and give pertinent dates, including estimated date of starting al-depths for all markers and zones pertinent to this work (*	Europeration of Recompetion Report and Log form (any proposed work. If well is directionally druled,
 This well was commenced in Nov. 1974. 8 5/8" 24 & 32# pipe was set at 460' and cement circulated. 5 1/2"14# casing was set at 2042' and cemented with 50 SX. Top of cement in annulus calculated 1742'. Drilled and tested - no leaks. Held 1000#. Drilled from 2042' to 2080' TD, completed open hole. Propose to P&A within 30 days of approval, as follows: A. Set 120' cement plug from 2057' (top of pay) to 1937'. Allow to set and tag cement. Gut 5 1/2" casing at 1260' and pull. Set 110' cement plug 1/2 in and 1/2 out of 5 1/2" casing stub. Top cement Est. 1200'. D. Set 100' cement plug from 510' up to 410'. Let cement set and tag cement. E. Set 50' cement plug in 5 1/2" up to surface and set 4 1/2" app 4' above ground. F. Location will be leveled and cleaned. 		
14 I hereby certify that the foregoing is true and currect Signed <u>Chamfes US</u> Thinks (This space for Federal or State office use) Approved by Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person	Title Operator APPROVED PETER W. CHESTER Title JUN 1 7 1993	June 10, 1993
or representations as to any matter within its jumediction.	BUREA HILDE WATERS to any department or seency of the United MANAGEMENT MANAGEMENT *See Instruction on Reveal Side	



.

2000 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 -1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 -