

N. M. O. C. G. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIPLICATE*
(Other instructions on
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. 111 0199827 -A
2. NAME OF OPERATOR Dalgort Oil Corp.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 3471 First National Bank Bldg., Dallas, Texas 75202	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 19° 10' N. 90° 00' W.	8. FARM OR LEASE NAME Federal-4
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 1-150-300
	12. COUNTY OR PARISH Cibola
	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
(Other) ☐ production casing	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-27-74 ID 2240. Van Wolex acoustic-gamma log.

12-28-74 Ran 56 joints new 4 1/2"-9.5", J-55 to 2240. Insert float at top of bottom joint, 10 scratchers, 5 centralizers. B-J cement w/125 gr 114, 150 gr 10, 50% por, 50 salt/cack, 20 gel, 75 gal acetic acid. Pumped plug down with 10" brine. Plug down 1:00 P.M.

12-31-74 Ran Western tie-in log. Perf w/J-II strip 2143-50, 2151-52, 2154-57, extra holes 2146, 2155, total 24 shots. Ran 50 joints regular + 15 joints 2 3/8" upset. Total tbq 2113.52, B/A 2126.88 g.m. Acidized w/1000 gal 12%, in vacuum in 5".

RECEIVED
JAN 13 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, N.M.

18. I hereby certify that the foregoing is true and correct.

SIGNED <i>John M. Lamp</i>	TITLE geologist	DATE 1-8-75
(This space for Federal or State office use)		

APPROVED BY <i>H. L. BEEKMAN</i>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

RECEIVED

JAN 15 1975

OIL CONSERVATION COMM.
HOBBS, N. M.

RECEIVED

JAN 15 1975

O. C. C.
ARTESIA, OFFICE