

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 16816A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry hole

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

Room 711, Phillips Bldg., Odessa, Texas 79761

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

(Unit B) 660' FN & 1980' FE lines

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

dated 6-5-75

4380' Gr., 4390' DF

19, 8-S, 32 E

12. COUNTY OR PARISH 13. STATE

Chaves New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Prepare plug and abandon as follows:

1. Pull rods and pump.
2. Load hole with mud mixed 25 sx salt gel per 100 barrels brine or produced water.
3. Spot 35 sx Class H cement from approximately 4166' to 3850' (perms 4108'-4141')
4. Spot 25 sx Class H cement from approximately 2160' to 1840'. 1500 TO 1800
5. Spot 10 sx Class H cement in at surface in 4 1/2" casing
6. Install well marker.
7. Fill and level pits and clear location.

Field Representative: E. T. Millholon, telephone 393-3664.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Engineering Advisor

DATE 12-2-75

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED  
AS AMENDED  
DEC 5 1975  
ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side